

Slide Rails

Medium Load, Steel, Stainless Steel

Load Rating: 225N~481N/2 pcs.

■Features: The rails are trivalent chrome coated steel. Economically priced slide rails compliant with RoHS regulations.

■Steel, Two-Step **SR36** Rail Disassembly: **Possible**

RoHS Inner and outer rails are not exchangeable.

Material: Steel
Surface Treatment: Bright Chromate (Trivalent Chromium)

Part Number	Rail Length	Stroke	A	B	C	D	E	F	G	Load Rating (N/2 pcs.)	Unit Price	Volume Discount Rate
SR36												
12	305	229	-	152.4	254	-	149.2	260.3	273	294	1 ~ 5 pc(s)	6 ~ 20 pcs
14	356	279	-	203.2	304.8	-	200	311.1	323.8	363		
16	406	305	-	254	355.6	-	250.8	361.9	374.6	382		
18	457	330	203.2	304.8	406.4	212.7	301.6	412.7	425.4	362		
20	508	381	228.6	355.6	457.2	238.1	352.4	463.5	476.2	323		
22	559	406	254	406.4	508	263.5	403.2	514.3	527	304		
24	610	432	279.4	457.2	558.8	288.9	454	565.1	577.8	265		
26	660	483	304.8	508	609.6	314.3	504.8	615.9	628.6	235		
28	711	508	330.2	558.8	660.4	339.7	555.6	666.7	679.4	225		

For horizontal installation, the target value of load rating is 25% (Reference Value).
The rails stop once in the full stroke position. The inner and outer rails can be separated by pulling further.

■Features: The rails are made of EN 1.4301 Equiv., which has excellent corrosion resistance.

■Stainless Steel, Two-Step **SSRN36** Rail Disassembly: **Not Possible**

RoHS Inner and outer rails are not exchangeable.

Material(Rail): EN 1.4301 Equiv.
Ball: EN 1.4125 Equiv.

Part Number	Rail Length	Stroke	A	B	C	D	E	F	G	Load Rating (N/2 pcs.)	Unit Price	Volume Discount Rate
SSRN36												
12	304.8	228.6	-	152.4	254	-	149.2	260.3	273	481	1 ~ 3 pc(s)	4 ~ 20 pcs
14	355.6	279.4	-	203.2	304.8	-	200	311.1	323.8	461		
16	406.4	304.8	-	254	355.6	-	250.8	361.9	374.6	422		
18	457.2	330.2	203.2	304.8	406.4	212.7	301.6	412.7	425.4	402		
20	508	381	228.6	355.6	457.2	238.1	352.4	463.5	476.2	363		
22	558.8	406.4	254	406.4	508	263.5	403.2	514.3	527	333		
24	609.6	431.8	279.4	457.2	558.8	288.9	454	565.1	577.8	294		
26	660.4	482.6	304.8	508	609.6	314.3	504.8	615.9	628.6	265		
28	711.2	508	330.2	558.2	660.4	339.7	555.6	666.7	679.4	245		

For horizontal installation, the target value of load rating is 25% (Reference Value). The rails can not be pulled apart.
Use M4 Recessed Truss Machine Screws (P2-233, 234) or Recessed Binding Head Screws (P2-232) to mount rails.

Ordering Example
Part Number
SSRN3628
SR3624

Slide Rails

Medium Load, Steel, Stainless Steel

Load Rating: 294N~588N/2 pcs.

■Features: The rails are trivalent chrome coated steel. Economically priced slide rails compliant with RoHS regulations.

■Steel, Three-Step **SRX36** Rail Disassembly: **Not Possible**

RoHS

Material: Steel
Surface Treatment: Bright Chromate (Trivalent Chromium)

Part Number	Rail Length	Stroke	A	B	C	D	Load Rating (N/2 pcs.)	Unit Price	Volume Discount Rate
SRX36									
12	305	324.2	-	149.2	260.3	273	500	1 ~ 5 pc(s)	6 ~ 20 pcs
14	356	375.4	-	200	311.1	323.8	529		
16	406	424.6	-	250.8	361.9	374.6	500		
18	457	475.8	212.7	301.6	412.7	425.4	461		
20	508	527	238.1	352.4	463.5	476.2	451		
22	559	578.2	263.5	403.2	514.3	527	402		
24	610	629.4	288.9	454	565.1	577.8	353		
26	660	678.6	314.3	504.8	615.9	628.6	333		
28	711	729.8	339.7	555.6	666.7	679.4	294		

For horizontal installation, the target value of load rating is 25% (Reference Value).
Three-step rail can be pulled out to the end. The rails can not be pulled apart.
Use M4 Recessed Truss Machine Screws (P2-233, 234) or Recessed Binding Head Screws (P2-232) to mount rails.

■Features: The rails are made of EN 1.4301 Equiv., which has excellent corrosion resistance.

■Stainless Steel, Three-Step **SSRXN36** Rail Disassembly: **Not Possible**

RoHS

Material(Rail): EN 1.4301 Equiv.
Ball: EN 1.4125 Equiv.

Part Number	Rail Length	Stroke	A	B	C	D	Load Rating (N/2 pcs.)	Unit Price	Volume Discount Rate
SSRXN36									
12	304.8	327.2	-	149.2	260.3	273	588	1 ~ 5 pc(s)	6 ~ 20 pcs
14	355.6	378	-	200	311.1	323.8	578		
16	406.4	428.4	-	250.8	361.9	374.6	559		
18	457.2	479.2	212.7	301.6	412.7	425.4	549		
20	508.0	530	238.1	352.4	463.5	476.2	529		
22	558.8	580.8	263.5	403.2	514.3	527	500		
24	609.6	631.6	288.9	454	565.1	577.8	480		
26	660.4	682.4	314.3	504.8	615.9	628.6	461		
28	711.2	733.2	339.7	555.6	666.7	679.4	441		

For horizontal installation, the target value of load rating is 25% (Reference Value). Three-step rail can be pulled out to the end. The rails can not be pulled apart.
Use M4 Recessed Truss Machine Screws (P2-233, 234) or Recessed Binding Head Screws (P2-232) to mount rails.

Ordering Example
Part Number
SSRXN3620
SRX3624

