

DC 3-/4-wire Inductive Tubular Sensors

Tubular housings, Ø 4 mm, M4x0.5



Ø 4 mm	Ø 4 mm	Ø 4 mm	Ø 4 mm	M4x0.5
Flush	Flush	Non-flush	Non-flush	Flush
1.5 mm	1.5 mm	5 mm	5 mm	0.6 mm
0...1.2 mm	0...1.2 mm	0...4 mm	0...4 mm	0...0.42 mm
2X	2X	3X	3X	1X
BES00JA	BES00J6	BES012K	BES012H	BES01P0
BES 516-3007-G-E4-C-S4-00,3	BES 516-3007-G-E4-C-PU-02	BES G04ED-PSC50F-S26G	BES G04ED-PSC50F-EP02	BES M04EC-PSD06B-BP02
	BES00K5	BES012E	BES0127	
	BES 516-3017-G-E4-C-PU-02	BES G04ED-POC50F-S26G	BES G04ED-NSC50F-EP02	
	BES00JW	BES0129		
	BES 516-3008-G-E4-C-PU-02	BES G04ED-NSC50F-S26G		
	BES00KH	BES0125		
	BES 516-3018-G-E4-C-PU-02	BES G04ED-NOC50F-S26G		
10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC
3 V	3 V	2.5 V	2.5 V	2.5 V
75 V DC	75 V DC	75 V DC	75 V DC	75 V DC
100 mA	100 mA	100 mA	100 mA	100 mA
Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes	Yes/Yes/Yes
-25...+70°C	-25...+70°C	-25...+70°C	-25...+70°C	-25...+70°C
3 kHz	3 kHz	3 kHz	3 kHz	2 kHz
Yellow LED	Yellow LED	Yellow LED	Yellow LED	No
IP 67	IP 67	IP 67	IP 67	IP 67
CE, cULus	CE, cULus	CE, cULus	CE, cULus	CE, cULus
Slim design	Slim design	Slim design, large switching distance	Slim design, large switching distance	Slim design
Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
PBT	PBT	PET-C	PET-C	POM
0.3 m PUR cable with M12 connector, 4-pin	2 m PUR cable, 26 AWG	M5 connector, 4-pin	2 m PUR cable, 26 AWG	2 m PUR cable, 26 AWG
BCC M415-0000-1A-003-EX44T2-020		BKS-B 25-3-PU-03		



- Inductive sensors
- Global DC 3-wire
- DC 3-/4-wire Tubular housings
- Block housings
- DC 2-wire
- AC/DC 2-wire
- AC 2-wire
- Analog distance measurement
- Special properties
- Special accessories

