

## cylinder single acting series CMI



**description** cylinder single acting series CMI with spring return; industrial type; operating pressure max. 700bar; for any mounting position; threaded cylinder tube, mounting holes at the bottom; connection 3/8" NPT female thread; cylinder from CMI-50N100 on will be supplied with handle

**scope of supply** cylinder, high-pressure female coupling, dust protection

push force [kN]	stroke [mm]	oil capacity [ccm]	tube thread	base thread	type
49,5	25	18	M40x1,5	M6	CMI-5N25
49,5	50	35	M40x1,5	M6	CMI-5N50
49,5	75	53	M40x1,5	M6	CMI-5N75
49,5	125	88	M40x1,5	M6	CMI-5N125
49,5	175	124	M40x1,5	M6	CMI-5N175
49,5	225	159	M40x1,5	M6	CMI-5N225
111	25	40	M60x1,5	M8	CMI-10N25
111	50	80	M60x1,5	M8	CMI-10N50
111	100	159	M60x1,5	M8	CMI-10N100
111	150	238	M60x1,5	M8	CMI-10N150
111	200	318	M60x1,5	M8	CMI-10N200
111	250	398	M60x1,5	M8	CMI-10N250
232	25	83	M85x1,5	M10	CMI-25N25
232	50	166	M85x1,5	M10	CMI-25N50
232	100	332	M85x1,5	M10	CMI-25N100
232	150	498	M85x1,5	M10	CMI-25N150
232	200	664	M85x1,5	M10	CMI-25N200
232	250	830	M85x1,5	M10	CMI-25N250
232	300	996	M85x1,5	M10	CMI-25N300
496	50	354	M125x2	M12	CMI-50N50
496	100	709	M125x2	M12	CMI-50N100
496	150	1063	M125x2	M12	CMI-50N150
496	325	2304	M125x2	M12	CMI-50N325
929	100	1327	M168x2	M12	CMI-100N100
929	150	1991	M168x2	M12	CMI-100N150

illustrations are non-binding  
all designs, configurations, measurements and materials are subject to change without prior notice