

**ABMESSUNGEN uniGEAR SCHNECKENGETRIEBEMOTOREN NMS BAUGRÖÖE 25 - 63**

Bau- größe	A	C	D	b	t <sub>1</sub>	E	F	G	G <sub>1</sub>	H	I	K	α	KE	L	M	N	N <sub>1</sub>	O	P	Q	R	S	T	V	Motor	X*	X <sub>b</sub>	Y*	Z*	kg
<b>NMS 25</b>	45	71	11 (H8)	4	12,8	83	22	45	50	35	25	34	10°	3 x Ø6,5	42	55	45 (-0,2)	22,5	6	64	35,5	48	5	16	22,5	50L	144	182	98	80	3,0
																										56	167	193	110	110	3,5
<b>NMS 30</b>	54	80	14 (H8)	5	16,3	97	32	55	63	40	30	44	0°	4 x M6 x 11	56	65	55 (h8)	29	6,5	75	44	57	5,5	21	27	50L	144	182	98	80	3,6
																										56	167	193	110	110	4,1
																										63	193	218	123	115	5,6
<b>NMS 40</b>	70	100	18 (H8)	6	20,8	121,5	43	70	78	50	40	60	45°	4 x M6 x 8	71	75	60 (h8)	36,5	6,5	87	55	71,5	6,5	26	35	56	167	193	110	110	5,2
																										63	193	218	123	115	6,7
																										71	215	246	138	125	8,4
<b>NMS 50</b>	80	120	25 (H8)	8	28,3	144	49	80	92	60	50	70	45°	4 x M8 x 10	85	85	70 (h8)	43,5	8,5	100	64	84	7	30	40	63	193	218	123	115	7,9
																										71	215	246	138	125	9,6
																										80	235	277	156	140	14
<b>NMS 63</b>	100	144	25 (H8)	8	28,3	174	67	95	112	72	63	85	45°	8 x M8 x 14	103	95	80 (h8)	53	8,5	110	80	102	8	36	50	71	215	246	138	125	12
																										80	235	277	156	140	16
																										90S	250	292	176	144	18
																										90L	275	316	176	144	21

Alle Maße in mm; Abmessungen freibleibend; technische Änderungen vorbehalten!

\*) je nach Motorfabrikat