

Temperature sensors with switch point

Connector bayonet according to ISO 15170

Thread/HEX	thermal conductivity probe	Switch point	Function	Hysteresis	Electric potential	Check values at	Order number
5/8"-18UNF / 27	11 mm	105°C	normally open	15 K	Low side switch	20 °C-698Ω ± 65Ω 60 °C-144Ω ± 12Ω 100 °C-39,6Ω ± 3Ω	422 319



Connector bayonet 10SL plastic

Thread/HEX	thermal conductivity probe	Switch point	Function	Hysteresis	Electric potential	Check values at	Order number
M 14 x 1,5 / 19	15 mm	100°C	normally open	≤ 20 K	Low side switch	20 °C-698 Ω ± 74 Ω 60 °C-144 Ω ± 12 Ω 100 °C-39,6 Ω ± 3 Ω	422 333



Connector minitimer 2,8 x 0,8

Thread/HEX	thermal conductivity probe	Switch point	Function	Hysteresis	Electric potential	Check values at	Order number
M 14 x 1,5 / 19	13 mm	110°C	normally open	≤ 20 K	Low side switch	20 °C-698 Ω ± 65 Ω 60 °C-141 Ω ± 12 Ω 100 °C-39,6 Ω ± 3 Ω	422 229

