

DLF

Pressure transmitter for liquid medium

thermokon
HOME OF SENSITIVE TECHNOLOGY

Datasheet

Subject to technical alteration
Issue date: 06.07.2018 • A002



Application

For pressure detection in liquid mediums for air conditioning, heating and water application. Suitable for plants with refrigerant.

Types Available

Pressure transmitter – active 0..10 V | 4..20 mA

DLF<range> V G1/4"
DLF<range> A G1/4"

DLF<range> V G1/2"
DLF<range> A G1/2"

<range> measuring ranges: 0..4 (0..58) | 6 (87) | 10 (145) | 16 bar (232 psi)...other measuring ranges please request

Security Advice – Caution



The installation and assembly of electrical equipment should only be performed by authorized personnel.

The product should only be used for the intended application. Unauthorised modifications are prohibited! The product must not be used in relation with any equipment that in case of a failure may threaten, directly or indirectly, human health or life or result in danger to human beings, animals or assets. Ensure all power is disconnected before installing. Do not connect to live/operating equipment.

Please comply with

- Local laws, health & safety regulations, technical standards and regulations
- Condition of the device at the time of installation, to ensure safe installation
- This data sheet and installation manual

Notes on Disposal



As a component of a large-scale fixed installation, Thermokon products are intended to be used permanently as part of a building or a structure at a pre-defined and dedicated location, hence the Waste Electrical and Electronic Act (WEEE) is not applicable. However, most of the products may contain valuable materials that should be recycled and not disposed of as domestic waste. Please note the relevant regulations for local disposal.

Technical Data

Measuring values	pressure	
Medium	fluids, air or other non-flammable/non-aggressive gases	
Output Voltage	0...10 V, min. load 5 k Ω	
Output Amp	4...20 mA, max. load 500 Ω	
Power supply	V 15...24 V = ($\pm 10\%$) or 24 V ~ ($\pm 10\%$)	A 15...24 V = ($\pm 10\%$)
Power consumption	V typ. 0,15 W (24 V ~) 0,3 VA (24 V ~)	A typ. 0,5 W (24 V ~)
Working range temp.	-40...+125 °C	
Measuring range pressure	depending on device	
Accuracy pressure	$\pm 0,5\%$ (typ. at +21 °C)	
Max. working overpressure	2-fold nominal pressure	
Enclosure	wetted parts stainless steel V2A	
Protection	IP65 according to EN 60529	
Cable entry	compression fitting for cable max. $\varnothing \pm 8$ mm	
Connection electrical	connector M5S according to EN175301-803	
Connection mechanical	G 1/4", G 1/2"	
Ambient condition	-40...+105 °C	
Weight	approx. 60 g	
Notes	other measuring ranges please request, adaptor to 3/2" available	

Mounting Advices

- For connection the device the device, all process lines must be depressurised
- Consider the suitability of the device for the medium to be measured
- Consider maximum pressure
- For screwing use only the spanner flat of the stainless steel body.
Never turn the sensor on the plastic ring.

