

# MOTORE ELETTRICO ELECTRIC MOTOR ELEKTROMOTOR

Motori C.A. / A.C. motor / W.S. Motor

	CODICE CODE KODE	Poli Poles Polig	Potenza Power Nennleistung (KW)	n° di giri rpm Upm (giri/min)	Assorbimento (Ampere)		Rapporto CA/CN	Tipo di servizio Type of duty Betriebsart (giri/min)	Dimensioni Dimensions Masse		Pos.
					230V	400V			A	B	
Motore C.A. trifase A.C. threephase motor Wechselstrommotor Drehstrom	624	6	0.55	920	3.6	2.1	1.8	S3-30%	168	141	1
	425	4	0.75	1400	4.1	2.4	2.8	S3-30%	163	141	1
	426	4	1.10	1400	4.6	2.7	2.3	S3-30%	168	141	1
	427	4	1.50	1400	5.25	3.04	2.3	S3-30%	183	141	1
	428	4	2.20	1380	9.6	5.6	2.1	S3-30%	198	141	1
	429	4	3.00	1380	12.8	7.4	2.0	S3-30%	218	141	1
	430	4	4.00	1390	17	9.8	1.8	S3-30%	243	141	1
	431	4	5.20	1380	22.2	12.8	1.8	S3-30%	268	141	1
	432	4	7.50	1380	27.5	16.0	1.8	S3-30%	vedi disegno		2
Motore C.A. monofase A.C. singlephase motor Wechselstrommotor Einphase	445	4	0.75	1400	6		0.85	S3-30%	183	141	1
	446	4	1.10	1380	11		0.78	S3-30%	198	141	1
	447	4	1.50	1400	12		0.80	S3-30%	218	141	1

Motori a c.a. trifasi 230-400 V 50 Hz  
e monofasi 220 V 50 Hz  
Isolamento classe H.  
Protezione motore IP10.  
Tensione di funzionamento :  $\pm 5\%$

A.C. Threephase motors 230-400 V 50 Hz  
and singlephase 220V 50 Hz  
Insulation class H.  
Protection motor IP10.  
Voltage :  $\pm 5\%$

W.S. Drehstrom Asynchronmotor 230-400V 50Hz  
W.S. Einphasen Asynchronmotor 220V 50Hz  
Isolierung Klasse H.  
Schutzart motor IP10.  
Spannungstoleranz  $\pm 5\%$

Pos. 1

