

# 2408 : Powered Hydraulic Bender

## The + product :

### Bending capacity:

**Gas pipes:** Ø 3/8" to 4" (nfa 49115 - en 10255).

**Locksmith's pipes:** Ø 12 à 45 mm.

**Bending angle:** 0° to 90°.

## Description

### For medium and heavy series gas pipes.

Electrical hydraulic bender for worksites or prefabrication.

Simple action circuit with spring-loaded piston return.

Supplied in a wooden case with the forms and accessories.

Less effort required for large batches.

Limit switch (option - ref. 240811) to reproduce identical bends.

To identify the different types of cheeks, see next pages.


### Tip:

- Use Virax hydraulic ram oil for best protection.

- All necessary precautions must be taken when filling the ram to avoid foreign matter entering the reservoir as this may impair operation.

- Use horizontally.

Ref. 240851, Ref. 240852 delivered in two wooden chests



## References

SKU	For pipe	Formers	Ram	Type	kg
240842	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	230 V - n° 2	Open Cheeks	93,000
240843	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2"	230 V - n° 2	Sliding Cheeks	87,000

<b>Sku</b>	<b>For pipe</b>	<b>Formers</b>	<b>Ram</b>	<b>Type</b>	<b>kg</b>
<b>240851</b>	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3 - 3.1/2 - 4"	230 V - n° 3	Hinged Cheeks	303,000
<b>240852</b>	Steel	3/8 - 1/2 - 3/4 - 1 - 1.1/4 - 1.1/2 - 2 - 2.1/2 - 3"	230 V - n° 3	Hinged Cheeks	188,000

