



SPECIFICATION

POWER SOURCE : <input type="checkbox"/> AC 110/220V ±10%, 50/60Hz <input type="checkbox"/> DC 24V
POWER CONSUMPTION : approx. 3VA
OUTPUT : Potential free change over contact
RESPONSE TIME : approx 0.2m sec
CONTACT RATING : AC 250V, 5A max.
AMBIENT TEMP. : -20 ~ +60°C

ELECTRODE DATA

SWITCHING : Operating resistance 0~5KΩ	
SENSITIVITY (NORMAL) : Return resistance 20KΩ over	
MEASURING CIRCUIT	Normal sensitivity AC 6V
CURRENT & VOLTAGE	High sensitivity AC 12V

\* P : PUMPING, D : DRAIN

	HITROL CO., LTD.					SCALE	UNIT	SHEET NO.
						N.S	mm	—
						PROJECT		
						DRAWING NO.		
						HLC-300-A-01		
NO.	DATE	REVISION	REV'D BY	CHK'D BY	APP'D BY	TITLE <b>CONTROL &amp; ALARM UNIT</b> <b>HLC-300</b>		
	SEP. 2016	1ST ISSUE	Y H LEE	B S SUNG	Y H KIM			

This drawing is the property of HITROL and shall not be copied, communicated, or given for tiers except with our written permission.