



IMPULSES FOR AUTOMATION with PC Control 645 and I/Os



2 versions of PC Control 645:


- Combimaster with FMS/DP functionality in the 500 kBaud range, also in combination with the I/Os of Kuhnke's Profi 690 to serve various decentralised automation purposes.
- Your entry into the world of 12 MBaud PROFIBUS technology: DP monomaster functionality in combination with the I/Os of Profi 690 E+.





Kuhnke GmbH Lütjenburger Straße 101 D-23714 Malente

Phone Int+49+4523402-0 Fax Int+49+4523402247 Internet http://www.kuhnke.de e-mail sales@kuhnke.de



Technical data

Processor SAB 165 or SAB 167

Execution time per logic command - 450 ns

16 bit add/sub - 450 ns 16 bit mul/div - 3 μs

Memory 320 kByte flash EPROM/80 kByte RAM

Commands extended PLC instruction set/C-tasks

Special functions programming of other Kuhnke controllers

via PROFIBUS

Application in PC: supply via PC or external supply with 24 V

separate: external supply with 24 V DC

Interfaces PROFIBUS-DP max. 12 MBaud or

- DP/FMS max. 500 kBaud V.24, max. 57.5 kBaud

Dual-port RAM

System

Programming KUBES

Network configuration VEBES

Inputs/outputs Profi I/O 690E, Profi I/O 690E+

Profi Control 680S

PLC Profi Control 680I, Compact Control 680C, KDT 680CT

Modu Control 657P, PC Control 645

Devices Servo Control 681M

Micro valve island

and third party PROFIBUS components

Гуре	Description	Order No.
		645.425.01 645.425.11

with external supply:

Р

PC Control 645-500 NT | PROFIBUS-FMS/DP combimaster, max. 500 kBaud | 645.425.02 PC Control 645-12M NT | PROFIBUS-DP master, max. 12 MBaud | 645.425.10

CAN and other bus systems upon request

This data sheet is primarily intended for the use by design, project, and development engineers. It does not give any information about delivery possibilities. Data is only given to describe the product and must not be regarded as guaranteed properties in legal sense. Any claims for damages against us — on whatever legal grounds — are excluded except in instances of deliberate intent or gross negligence on our part. We reserve the rights for errors, omissions and modifications.