



ROSTFREI  
Inox  
Stainless  
Steel

Inch  
sizes  
available

**3 Type**

- E** with threaded blind bore
- C** with plain blind bore, Tol. H7

d <sub>1</sub>	d <sub>2</sub>			d <sub>3</sub> H7		d <sub>4</sub>	h <sub>1</sub>		h <sub>2</sub>		h <sub>3</sub>	t min.
	GN 6336.1	GN 6336.2	Thread (Type E)	Bushing Steel	Bushing Stainless Steel		GN 6336.1	GN 6336.2	GN 6336.1	GN 6336.2		
32	M 6	-	M 6	B 6	-	12	21	20	10	10	8,5	12
40	M 6	M 8	M 8	B 6	B 8	14	26	26	13	13	10	14
50	M 8	M 10	M 10	B 8	B 10	18	34	32	17	17	10	18
63	M 10	M 12	M 12	B 10	B 12	20	42	40	21	21	14	22
80	M 12	M 16	M 16	B 16	-	25	52	52	25	27	15	30

**Ausführung**

- **GN 6336.1**  
Plastic  
Duroplast (PF)  
black, shiny finish  
Bushing  
- Steel zinc-plated, blue passivated —  
- Stainless Steel AISI 303 **NI**
- **GN 6336.2**  
Plastic  
Technopolymer (Polyamide PA)  
- shock-resistant  
- black, matt finish  
Bushing  
- Steel zinc-plated, blue passivated —  
- Stainless Steel AISI 303 **NI**
- *ISO-Fundamental Tolerances* → Page 1132
- *Plastic characteristics* → Page 1141
- **RoHS compliant**

**Information**

Star knobs GN 6336.1 / GN 6336.2 with protruding steel bushing have important advantages:

The face of the bushing is exactly square to the bore and is with the complete diameter out of steel or Stainless Steel. The protruding steel bushing allows a perfect cross-dowels connection.

see also...

- *Star knobs GN 6336 (Cast iron / St. Steel / Aluminium)* → Page 274
- *Star knobs DIN 6336 (Plastic, without protruding bushing)* → Page 275

How to order (Duroplast, bushing Stainless Steel)

1	d <sub>1</sub>
2	d <sub>2</sub> (d <sub>3</sub> )
3	Type
4	Material bushing

**GN 6336.1-50-M10-E-NI**

How to order (Technopolymer, bushing steel)

1	d <sub>1</sub>
2	d <sub>3</sub> (d <sub>2</sub> )
3	Type

**GN 6336.2-40-B8-C**