

Product name VEGASWING 51
 Model code SG51.XXSGBTPM
 eID DE49592127
 Quantity 1

Vibrating level switch for liquids

Application area

VEGASWING 51 is used as a universal level switch in liquids with small dimensions. Independent of the mounting position, it detects reliably with millimetre accuracy the limit level. The instrument can be used as empty or full detector, as approved overfill protection, dry run protection or pump protection in vessels and pipelines. The VEGASWING 51 is an economical solution with maximum reliability and safety.

Your benefit

- Minimum time and cost expenditure thanks to simple setup without medium
- Precise and reliable function due to product-independent switching point
- Low maintenance costs

Price list: Standard-10/04/2018-DE-€

Approval directive / Scope		None / World-wide
Approval	XX	without
Version / Process temperature	S	Standard / -40...+100°C
Process fitting / Material	GB	Thread G $\frac{3}{4}$ PN64, DIN3852-A / 316L
Electronics	T	Transistor PNP 9.6 ... 35 V DC
Housing	P	316L
Electrical connection / Protection	M	M12x1 / IP67
Switching point		Standard
Operating instructions		DE - German
Number of Operating Instructions manuals		1
Measurement loop identification label		without
Additional cleaning procedure		without
Certificate / Standard		without
Foodstuff/Pharmaceutical certificate		without
Setting of the density range		Standard sensitivity (from density 0.7 g/cm ³)
Switching delay in seconds		0,5
Recommended welded socket (not in scope of delivery)		ESTSG.1GB**
Customs tariff number (HS code)		90261029