


REDUCTION GEAR UNIT	Ratio		Rated input		Rated input power	Rated output torque	Weight	Lubricant						
	i		r.p.m.	HP				da Nm	Kg	Oil <input checked="" type="checkbox"/>	Grease <input type="checkbox"/>			
	1.88	: 1	540	130	95.6			SAE.140EP	Quantity Lt.					
Gear Arrangement	Bevel couplings				Cylindrical couplings				Bearings					
	In. 	Helicoidal	Teeth number			Module	Helicoidal	Teeth number			Module	A	32210	
Straight		Z 1	Z 2	Z 3	Z 4	M.	Straight	Z 1	Z 2	Z 3	Z 4	M.	B	32210
	*	14	29			8.3	*	29	32				C	30215
													D	32215
													E	30216
													F	30215
													G	
													H	
Components material														
Casing	Shaft X	Shaft Z		Bevel gear		Spur gear								
GS 400/12 UNI 4544_74	20 MnCr5	18 NiCrMo5		18 NiCrMo5		20 MnCr5								

COMER INDUSTRIES reserves the right to make any change to this product without prior public acknowledgement

COMER INDUSTRIES S.p.A. 42046 Villanova di Reggiolo (R.E.) Italia Tel. 0522\974111 (9 Linee) Telefax 0522\973249