

OLI



MVE 500/15E-40A0 (EE40050040A0JA0000)

3 PH - 4 poles - 1500 RPM -
220-240/380-415 V - 50 Hz








Working moment (Kg*cm)	Unbalance (Kg*cm)	Centrifugal force (Kg)	Nominal voltage (V)	Input power (kW)	Current (A)	Power Factor	Ia/In
40,12	20,06	504	220-240/380-415	0,35	Δ 1,83 Y 1,06	0,48	3

OVERALL DIMENSIONS (mm)													
Weight (Kg)	A	B	G	Holes number	C	D	E	F	H	I	L	M	N
21	105	140	13	4	330	170	196	20	92	174	166	78	160

TECHNICAL FEATURES							
Type of grease	Greased for life	Screw	Washer	Clamping torque (Nm)		Cable type	Cable gland
/	Yes	M12	13 x 24 mm	80		4G2.5 80°C	M20 80°C

BEARINGS			
Type	Life 100%	Life 80%	Life 50%
6306 2Z	8681	16956	69452

CERTIFICATION	
<p>ATEX II2 D Ex tb IIIC T135°C Db IP66 IECEX Ex tb IIIC T135°C Db IP66 CLASS II DIV.2 GROUP F,G T4 Ex tb IIIC Tx Db IP66 CONF.TO UL1004-3, UL1004-1,UL 60079-0,UL60079-31 CERT. CSA C22.2 No.100,CSA C22.2 No.77, CSA C22.2N.60079-0,CSA C22.2N. 60079-31 T.Amb -20/+40°C</p>	    

REV.0-n/a