




# SPECIFICATION

Model Name		PT056-AST
Sub-Models		2
Display	Size	5.6"
	Max. Resolution	320*234
	Type	TFT LCD with LED Backlight
	Max. Colors	16-bit
	Backlight Life (hr)	20,000
	Display Contrast	300:1
	Luminance (cd/m2)	200
Touch Panel		4-wire Analog Resistive Type
CPU		RISC ARM9 32Bit
Backup SRAM		128KB (Optional: 1MB)
Working Memory		32MB
Built-in Storage Memory		8MB + 128MB (NAND Flash)
Real-Time Clock (RTC)		YES
Communication Interface	Micro SD Slot	YES
	USB Client	YES (USB 2.0)
	USB Host	YES (USB 1.1)
	Serial (Com1)	RS232/422/485
	Serial (Com2)	A-RS422/485 B-RS232/485 C-RS232 with RTS&CTS
	Serial (Com3)	RS232 (optional: RS485)
	Serial (Com4)	N/A
	Ethernet	N/A
Front Function Keys		N/A
Audio Out (optional)		N/A
Video In (optional)		N/A
Front USB Host Port		N/A
Power	Input	24VDC±10% Isolated
	Consumption	13W
Environment	Operating Temperature	-10°C~60°C
	Relative Humidity	10%~90%
	Shock (operation)	10 ~ 55Hz (X,Y,Z direction, 1G, 30 minutes shock test)
	EMI	FCC Part 15 Class A
	CE	EN61000-6-2, EN61000-6-4
	UL Certification	N/A
	Ingress Protection	IP66
Cooling		Natural Cooling
Dimension WxHxD (mm)		188.0 x 143.3 x 36.0
Cutout Dimension WxH (mm)		175.0 x 132.5
Net Weight (Kg)		0.59



Pericom AG

Waldstr. 7 D-78262 Gailingen t 07734 48 70 343

Moskau 314B CH 8262 Ramsen t 052 740 00 55

www.pericom.biz  
info@pericom.biz