

Wireless module - FL WLAN 1101 - 2702538

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



WLAN access point, client for USA and Canada, with two internal antennas for single-hole mounting, IP54, WLAN 802.11 a, b, g, n, frequency: 2.4 GHz, 5 GHz, connections: COMBICON 9 ... 32 V DC, RJ45: for LAN, web, http/https, Command Line Interface



Key Commercial Data

| | |
|--------------------------------------|---------------|
| Packing unit | 1 pc |
| GTIN | |
| GTIN | 4055626279398 |
| Weight per Piece (excluding packing) | 366.800 g |
| Weight per piece (including packing) | 366.800 g |
| Custom tariff number | 85176200 |
| Country of origin | Germany |

Technical data

Note

| | |
|-------------------|--|
| Trade restriction | The products are offered exclusively for export outside the EU and the European Economic Area. |
|-------------------|--|

Dimensions

| | |
|--------------------|--------------------|
| Width | 62.8 mm |
| Height | 36.5 mm |
| Depth | 113.2 mm |
| Note on dimensions | Outside dimensions |

Ambient conditions

| | |
|--|---|
| Ambient temperature (operation) | 0 °C ... 60 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C |
| Permissible humidity (operation) | 5 % ... 95 % (non-condensing) |
| Permissible humidity (storage/transport) | 5 % ... 95 % (non-condensing) |
| Air pressure (operation) | 800 hPa ... 1080 hPa (up to 2000 m above sea level) |

Wireless module - FL WLAN 1101 - 2702538

Technical data

Ambient conditions

| | |
|----------------------------------|---|
| Air pressure (storage/transport) | 660 hPa ... 1080 hPa (up to 3500 m above sea level) |
| Degree of protection | IP54 |
| Note | Degree of protection when installed |

Wireless interface

| | |
|--|--|
| Designation | Wireless LAN |
| Wireless standard | IEEE 802.11 |
| | a |
| | b |
| | g |
| | n |
| Antenna connection method | (Internal) |
| Frequency band | 2.4 GHz |
| | 5 GHz |
| Transmission power | max. 20 dBm (EIRP) |
| Number of wireless interfaces | 1 IEEE 802.11 a/b/g/n |
| Wireless modules that can be connected | 10 (In Access Point mode max. 2 SSIDs) |

Functions

| | |
|--------------------------|--|
| Operating modes | Access Point / Client Adapter / Repeater |
| Configuration | Web-based management, automated CLI |
| Quality of service (QoS) | Yes |
| Security | 802.11i |
| | WPA PSK (pre-shared key) |
| | WPA2 |
| | AES |
| | TKIP |
| | MAC filter |

Wireless card

| | |
|-----------------------|---|
| Number | 1 |
| Type | IEEE 802.11 a/b/g/n 2.4 GHz and 5 GHz to 300 Mbps |
| Assembly instructions | Permanently installed |

Antenna

| | |
|-------------------------------|-----------------------|
| Assembly instructions | Internal antenna |
| Number | 2 |
| Connection method | permanently installed |
| Note on the connection method | MIMO |
| Gain | 5 dBi |

Ethernet interface

| | |
|-----------|-----------------|
| Interface | Ethernet (RJ45) |
|-----------|-----------------|

Wireless module - FL WLAN 1101 - 2702538

Technical data

Ethernet interface

| | |
|-------------------------------|-----------------------------------|
| Number of interfaces | 1 |
| Connection method | RJ45 |
| Note on the connection method | Auto negotiation and autocrossing |
| Transmission speed | 10/100 Mbps |
| Transmission physics | Copper |
| Transmission length | 100 m (per segment) |

Power supply for module electronics

| | |
|-------------------------------|---|
| Connection method | Push-in spring connection |
| Designation | 1966101 FMC 1,5/ 3-STF-3,5 |
| Number of positions | 3 |
| Cross section range AWG | 24 ... 16 (Use copper wires rated 75° C (UL)) |
| Note on the connection method | Recommended conductor cross section: 0.75 mm ² |
| | Recommended ferrule: connection length 10 mm |
| | Recommended crimping pliers: trapezoidal or square |
| Supply voltage | 24 V DC (SELV) |
| Supply voltage range | 18 V DC ... 32 V DC (PELV/SELV) |
| | 9 V DC ... 32 V DC (PELV/SELV (as of HW version 05)) |
| Supply current | typ. 120 mA (at 24 V DC) |
| Current consumption | max. 250 mA (at 18 V DC) |
| | max. 400 mA (at 9 V DC) |

Connection data

| | |
|---------------------------------------|----------------------------|
| Designation | 1966101 FMC 1,5/ 3-STF-3,5 |
| Connection method | Push-in spring connection |
| Conductor cross section solid min. | 0.2 mm ² |
| Conductor cross section solid max. | 1.5 mm ² |
| Conductor cross section flexible min. | 0.2 mm ² |
| Conductor cross section flexible max. | 1.5 mm ² |
| Conductor cross section AWG min. | 24 |
| Conductor cross section AWG max. | 16 |
| Stripping length | 10 mm |

General

| | |
|---------------------|-------------------------------------|
| Mounting type | Single-hole mounting |
| Net weight | 366.8 g |
| Degree of pollution | 2 |
| Note | Degree of protection when installed |
| Wireless licenses | USA, Canada |
| Wireless licences | USA |
| | Canada |

Standards and Regulations

Wireless module - FL WLAN 1101 - 2702538

Technical data

Standards and Regulations

| | |
|-----------------------|-------------------------|
| Standards/regulations | FCC/CFR 47, Part 15.107 |
| Test result | Class B |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 24010504 |
| eCl@ss 4.1 | 24010504 |
| eCl@ss 5.0 | 19030112 |
| eCl@ss 5.1 | 19030100 |
| eCl@ss 6.0 | 19170200 |
| eCl@ss 7.0 | 19170201 |
| eCl@ss 8.0 | 19170201 |
| eCl@ss 9.0 | 19170201 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000817 |
| ETIM 4.0 | EC000816 |
| ETIM 5.0 | EC000816 |
| ETIM 6.0 | EC000816 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172710 |
| UNSPSC 7.0901 | 43223108 |
| UNSPSC 11 | 43172710 |
| UNSPSC 12.01 | 43223108 |
| UNSPSC 13.2 | 43223108 |

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approval details

Wireless module - FL WLAN 1101 - 2702538

Approvals

| | | | |
|-----------|--|---|---------------|
| UL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
|-----------|--|---|---------------|

| | | | |
|------------|--|---|---------------|
| cUL Listed | | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | FILE E 238705 |
|------------|--|---|---------------|

| | | | |
|--------------|--|--|--|
| cULus Listed | | | |
|--------------|--|--|--|

Accessories

Accessories

Adapter

Adapter - FL M32 ADAPTER - 2702544



Accessories for FL-WLAN 1100 series: Optional cable feed-through for sealing (IP67) the FL-WLAN 110x connection (IP20), if the device is not directly integrated onto the closed housing. Not needed when mounting on a control cabinet, etc.

Data plug

RJ45 connector - CUC-IND-C1ZNI-S/R4IE8 - 1421607



RJ45 connector, degree of protection: IP20, number of positions: 8, 1 Gbps, CAT5 (IEC 11801:2002), material: Zinc die-cast, connection method: IDC fast connection, connection cross section: AWG 26- 24, cable outlet: straight

Patch cable

Patch cable - FL CAT5 PATCH 1,5 - 2832221



Patch cable, CAT5, assembled, 1.5 m

PCB plug

Wireless module - FL WLAN 1101 - 2702538

Accessories

Printed-circuit board connector - FMC 1,5/ 3-STF-3,5 - 1966101

PCB connector, nominal current: 8 A, rated voltage (III/2): 160 V, number of positions: 3, pitch: 3.5 mm, connection method: Push-in spring connection, color: green, contact surface: Tin



Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>