


**MO-185-BL****MO-185-J****MO-185-R****MO-185-B****FIELD OF USE:**

**Safety industrial helmet with ARC FLASH integrated face shield.
Shockproof for the head, 1000 V insulating protection of the shell and eyes
and face protection of thermal effect due to an arc.**

RANGE :

- **MO-185-BL : white shell**
- **MO-185-BLM : white shell and shin strap**
- **MO-185-R : red shell**
- **MO-185-J : yellow shell**
- **MO-185-B : blue shell**

FEATURES:**• Shell:**

- IEC 397 - 440V.
- EN 50365 insulated 1000V AC, 150  DC.
- High density polypropylene helmet.
- Head base points to ensure a precise adjustment for a perfect fit and intermediate positions of the face shield.
- Deformable helmet in case of shock, equipped with a gutter.
- Adjustable size from 52 to 66 cm, adjustment of head rim at 5 mm intervals.
- 4 points textile head base, adjustable for a perfect fit.
- Frontal trimming.
- Textile with « clip » : MO-185-BL.
- Textile chin-strap with « clip »: MO-185-BLM.
- Recommended time of use: 5 years

• Face shield: Retractable face shield

- IEC 61482-1-2 class 1 (4kA-500ms \dot{E} 300mm-Energy 3.48 cal/cm²).
- GS-ET 29.
- Large polycarbonate face shield treated anti-scratch and anti-mist.
- Absorbs >99,9% of harmful UV radiation.
- 70% light transmission.
- Face shield totally retractable inside the helmet.
- Protection against ejections of molten metal (MM).
- EN 166 / EN 170 : 2-1.2. (U.V).
- Optical class : 2.
- Mechanical resistance: B.
- Protection against electrical arc of short-circuit: 8.
- Large polycarbonate face shield treated anti-scratch and anti-mist.
- Face shield totally retractable inside the helmet.

Approximate weight: 736gr

- Helmet certified  by Certotticca: certificate n° 02041

SPARE PARTS:

- **M-881838: reversible sticker**



- **M-87384: Protection**



- **MS-12: lamp 5 Leds**

