

HMT361 Humidity and Temperature Transmitter For wall mounting



Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT360	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	PRICE	
Transmitter unit	1 Transmitter type	HMT361	1												A	5	A	0		
	2 Parameters	RH+T RH+T+Td+a+Tw+x	A D																	
	3 Display	No display <i>Display on transmitter cover</i>	1 2																	
	4 Number of analog outputs	1 analog output channel (Ch1) 2 analog output channels (Ch1 + Ch2)	4... 20 mA 4... 20 mA	1 2																
	5 Parameter and scaling for 6 analog output (Ch1 & Ch2)	No analog output RH (0... 100%RH) T (choose range in next section) Td (-40...60°C) (-40...140°F) a (0... 160g/m3) (0...70gr/l3) Tw (0...60°C) (+32...+140°F) x (0...160g/kg d.a) (0...1120gr/lb) Special: Define quantity for: CH1: _____ CH2: _____ Define scale for: CH1: _____ CH2: _____																		
	NOTE:	- Td, a, Tw and x are only available with parameter selection D - If only one analog output has been chosen, choose A for Ch2																		
	7 Analog output range for temperature	-40...+60°C (-40...+140°F) -20...+60°C (-4...+140°F) 0...+60°C (+32...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -40...+80°C (-40...+176°F) -40...+120°C (-40...+248°F) 0...+100°C (+32...+212°F) -20...+180°C (-4...+356°F) -40...+180°C (-40...+356°F) 0...+180°C (+32...+356°F) Special																		
	8 Output units	Metric Non-metric		1 2																
	9 Interface cable connection	Cable gland M20x1.5 for cable diameters 7.5 ... 12 mm Conduit fitting NPT1/2" (for wire conduits) Cable gland M20x1.5 for cable diameters 10 ... 15 mm																		
	10 Ex certification and issuer	ATEX (VTT), Ex ia IIC T4 IECEX (VTT), Ex ia IIC T4 Factory Mutual (USA) CSA (Canada) TIIS (Japan) TR CU (EAC) KOSHA (Korea)																		
	11 User's guide	English German French Finnish Swedish Japanese Russian Chinese Korean																		
	12 Probe and cable length	HMP361 max +60°C																		
	13 Sensor type	HUMICAP 180R																		
	14 (blank)																			
	15 Sensor protection	PPS plastic grid & stainless steel netting (recommended choice) PPS plastic grid Sintered stainless steel filter Stainless steel grid filter	spare: DRW010281SP spare: DRW010276SP spare: HM47280SP spare: HM47453SP																	
	16 Probe installation accessories	None																		
TOTAL																				
QTY																				
TOTAL VALUE																				

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Installation accessories	
Galvanic Isolator	212483
Barrier	210664
Protection Cover	214101
Rain Shield	215109

Example of order code with typical settings:

HMT360	1	A	2	2	B	C	A	1	A	2	B	A	5	A	1	0
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

End customer: _____



Order form
Purchaser

Valid from February 2020
Order no.



HMT363 Humidity and Temperature Transmitter
For general use

Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT360	3	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	PRICE		
Transmitter unit	1 Transmitter type	HMT363	3																			
	2 Parameters	RH+T RH+T+Td+a+Tw+x	A D																			
	3 Display	No display Display on transmitter cover	1 2																			
	4 Number of analog outputs	1 analog output channel (Ch1) 2 analog output channels (Ch1 + Ch2)	4... 20 mA 4... 20 mA	1 2																		
	5 Parameter and scaling for 6 analog output (Ch1 & Ch2)	No analog output RH (0... 100%RH) T (choose range in next section) Td (-40...+100°C) a (0...500g/m3) Tw (0...+100°C) x (0...500g/kg d.a.)	(-40...+212°F) (0...218.5gr/lit3) (+32...+212°F) (0...3500gr/lb)		A B C H J K L X																	
	Special:	Define quantity for: Define scale for:	CH1: _____ CH2: _____ CH1: _____ CH2: _____																			
	NOTE:	- Td, a, Tw and x are only available with parameter selection D - If only one analog output has been chosen, choose A for Ch2																				
	7 Analog output range for temperature	-40...+60°C -20...+60°C 0...+60°C -20...+80°C -20...+120°C -40...+80°C -40...+120°C 0...+100°C -20...+180°C -40...+180°C 0...+180°C Special	(-40...+140°F) (-4...+140°F) (+32...+140°F) (-4...+176°F) (-4...+248°F) (-40...+176°F) (-40...+248°F) (+32...+ 212°F) (-4...+356°F) (-40...+356°F) (+32...+356°F)		A B C D E F G H J K L X																	
	8 Output units	Metric Non-metric		1 2																		
	9 Interface cable connection	Cable gland M20x1.5 for cable diameters 7.5 ... 12 mm Conduit fitting NPT1/2" (for wire conduits) Cable gland M20x1.5 for cable diameters 10 ... 15 mm			A B C																	
	10 Ex certification and issuer	ATEX (VTT), Ex ia IIC T4 IECEX (VTT), Ex ia IIC T4 Factory Mutual (USA) CSA (Canada) TIIS (Japan) TR CU (EAC) KOSHA (Korea)													2 3 4 5 7 8 A							
	11 User's guide	English German French Finnish Swedish Japanese Russian Chinese Korean													B C D E G J K V W							
12 Probe and cable length	2 m cable max 80°C 5 m cable max 80°C 10 m cable max 80°C 2 m cable max 120°C 5 m cable max 120°C 10 m cable max 120°C																					
13 Sensor type	HUMICAP 180R																					
14 (blank)																						
15 Sensor protection	PPS plastic grid & stainless steel netting (recommended choice) PPS plastic grid Sintered stainless steel filter Stainless steel grid filter																					
16 Probe installation accessories	None Duct Installation Kit																					
																		TOTAL				
																		QTY				
																		TOTAL VALUE				

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Installation accessories	
Galvanic Isolator	212483
Barrier	210664
Protection Cover	214101
Rain Shield	215109

Example of order code with typical settings:

HMT360 | 3 | **A** | 2 | 2 | **B** | **C** | **B** | 1 | **A** | 2 | **B** | 1 | 5 | **A** | 1 | **B**

End customer: _____

HMT364 Humidity and Temperature Transmitter

For high pressurized processes



Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT360	4	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	PRICE			
Transmitter unit	1 Transmitter type	HMT364	4																			
	2 Parameters	RH+T RH+T+Td+a+Tw+x	A D																			
	3 Display	No display <i>Display on transmitter cover</i>	1 2																			
	4 Number of analog outputs	1 analog output channel (Ch1) 2 analog output channels (Ch1 + Ch2)	4... 20 mA 4... 20 mA	1 2																		
	5 Parameter and scaling for 6 analog output (Ch1 & Ch2)	No analog output RH (0... 100%RH) T (choose range in next section) Td (-40...+100°C) (-40...+212°F) a (0...500g/m3) (0...218.5gr/lb) Tw (0...+100°C) (+32...+212°F) x (0...500g/kg d.a) (0...3500gr/lb) Special: Define quantity for: CH1: _____ CH2: _____ Define scale for: CH1: _____ CH2: _____																				
	NOTE:	- Td, a, Tw and x are only available with parameter selection D - If only one analog output has been chosen, choose A for Ch2																				
	7 Analog output range for temperature	-40...+60°C (-40...+140°F) -20...+60°C (-4...+140°F) 0...+60°C (+32...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -40...+80°C (-40...+176°F) -40...+120°C (-40...+248°F) 0...+100°C (+32...+ 212°F) -20...+180°C (-4...+356°F) -40...+180 °C (-40...+356°F) 0...+180°C (+32...+356°F) Special																				
	8 Output units	Metric Non-metric																				
	9 Interface cable connection	Cable gland M20x1.5 for cable diameters 7.5 ... 12 mm Conduit fitting NPT1/2" (for wire conduits) Cable gland M20x1.5 for cable diameters 10 ... 15 mm																				
	10 Ex certification and issuer	ATEX (VTT), Ex ia IIC T4 IECEX (VTT), Ex ia IIC T4 Factory Mutual (USA) CSA (Canada) TIIS (Japan) TR CU (EAC) KOSHA (Korea)																				
	11 User's guide	English German French Finnish Swedish Japanese Russian Chinese Korean																				
	12 Probe and cable length	2 m cable 5 m cable 10 m cable																				
	13 Sensor type	HUMICAP 180R																				
	14 (blank)																					
	Probe	15 Sensor protection	PPS plastic grid & stainless steel netting (recommended choice) PPS plastic grid Sintered stainless steel filter Stainless steel grid filter Membrane SST filter (for fuel cells)	<i>spare: DRW010281SP</i> <i>spare: DRW010276SP</i> <i>spare: HM47280SP</i> <i>spare: HM47453SP</i> <i>spare: 214848SP</i>	1 2 3 4 5																	
		16 Probe installation accessories	None Fitting Body NPT Fitting Body	<i>spare: 17223SP</i> <i>spare: 17225SP</i>	0 K G																	
TOTAL QTY																						
TOTAL VALUE																						

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Installation accessories

Galvanic Isolator	212483
Barrier	210664
Protection Cover	214101
Rain Shield	215109

Example of order code with typical settings:

HMT360 | 4 | A | 2 | 2 | B | C | A | 1 | A | 2 | B | E | 5 | A | 1 | K

End customer: _____

HMT365 Humidity and Temperature Transmitter

For high temperatures



		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	PRICE	
Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT360		5										5	A				
Transmitter unit	1 Transmitter type	HMT365																	
	2 Parameters	RH+T	A																
		RH+T+Td+a+Tw+x	D																
	3 Display	No display		1															
		<i>Display on transmitter cover</i>		2															
	4 Number of analog outputs	1 analog output channel (Ch1)	4... 20 mA			1													
		2 analog output channels (Ch1 + Ch2)	4... 20 mA			2													
	5 Parameter and scaling for 6 analog output (Ch1 & Ch2)	No analog output						A											
		RH (0... 100%RH)						B											
		T (choose range in next section)						C	C										
		Td (-40...+100°C)	<i>(-40...+212°F)</i>					H	H										
		a (0...500g/m3)	<i>(0...218.5gr/ft3)</i>					J	J										
	Tw (0...+100°C)	<i>(+32...+212°F)</i>					K	K											
	x (0...500g/kg d.a)	<i>(0...3500gr/lb)</i>					L	L											
	Special: Define quantity for:	CH1: _____	CH2: _____				X	X											
	Define scale for:	CH1: _____	CH2: _____																
NOTE:																			
- Td, a, Tw and x are only available with parameter selection D																			
- If only one analog output has been chosen, choose A for Ch2																			
							Ch1												
							Ch2												
7 Analog output range for temperature	-40...+60°C	<i>(-40...+140°F)</i>							A										
	-20...+60°C	<i>(-4...+140°F)</i>							B										
	0...+60°C	<i>(+32...+140°F)</i>							C										
	-20...+80°C	<i>(-4...+176°F)</i>							D										
	-20...+120°C	<i>(-4...+248°F)</i>							E										
	-40...+80°C	<i>(-40...+176°F)</i>							F										
	-40...+120°C	<i>(-40...+248°F)</i>							G										
	0...+100°C	<i>(+32...+ 212°F)</i>							H										
	-20...+180°C	<i>(-4...+356°F)</i>							J										
	-40...+180 °C	<i>(-40...+356°F)</i>							K										
	0...+180°C	<i>(+32...+356°F)</i>							L										
	Special								X										
8 Output units	Metric									1									
	Non-metric									2									
9 Interface cable connection	Cable gland M20x1.5 for cable diameters 7.5 ... 12 mm																		
	Conduit fitting NPT1/2" (for wire conduits)										A								
	Cable gland M20x1.5 for cable diameters 10 ... 15 mm										B								
											C								
10 Ex certification and issuer	ATEX (VTT), Ex ia IIC T4											2							
	IECEX (VTT), Ex ia IIC T4											3							
	Factory Mutual (USA)											4							
	CSA (Canada)											5							
	TIIS (Japan)											7							
	TR CU (EAC)											8							
	KOSHA (Korean)											A							
11 User's guide	English															B			
	German															C			
	French															D			
	Finnish															E			
	Swedish															G			
	Japanese															J			
	Russian															K			
	Chinese															V			
	Korean															W			
12 Probe and cable length	2 m cable																H		
	5 m cable																J		
	10 m cable																K		
13 Sensor type	HUMICAP 180R																5		
14 (blank)																		A	
15 Sensor protection	PPS plastic grid & stainless steel netting (recommended choice)																	1	
	PPS plastic grid																	2	
	Sintered stainless steel filter																	3	
	Stainless steel grid filter																	4	
16 Probe installation accessories	None																	0	
	Mounting flange																	D	
															TOTAL				
															QTY				
															TOTAL VALUE				

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Installation accessories

Galvanic Isolator	212483
Barrier	210664
Protection Cover	214101
Rain Shield	215109

Example of order code with typical settings:

HMT360	5	A	2	2	B	C	A	1	A	2	B	H	5	A	1	D
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

End customer: _____



HMT367 Humidity and Temperature Transmitter

For high humidities

Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT360	7										5	A			PRICE	
Transmitter unit	1 Transmitter type	HMT367	7															
	2 Parameters	RH+T RH+T+Td+a+Tw+x	A D															
	3 Display	No display <i>Display on transmitter cover</i>	1 2															
	4 Number of analog outputs	1 analog output channel (Ch1) <i>2 analog output channels (Ch1 + Ch2)</i>	4... 20 mA 4... 20 mA	1 2														
	5 Parameter and scaling for	No analog output																
	6 analog output (Ch1 & Ch2)	RH (0... 100%RH) T (choose range in next section) Td (-40...+100°C) <i>(-40...+212°F)</i> a (0...500g/m3) <i>(0...218.5gr/lit3)</i> Tw (0...+100°C) <i>(+32...+212°F)</i> x (0...500g/kg d.a) <i>(0...3500gr/lb)</i>																
	Special:	Define quantity for: Define scale for:	CH1: _____ CH2: _____ CH1: _____ CH2: _____															
	NOTE:	- Td, a, Tw and x are only available with parameter selection D - If only one analog output has been chosen, choose A for Ch2																
	7 Analog output range for temperature	-40...+60°C <i>(-40...+140°F)</i> -20...+60°C <i>(-4...+140°F)</i> 0...+60°C <i>(+32...+140°F)</i> -20...+80°C <i>(-4...+176°F)</i> -20...+120°C <i>(-4...+248°F)</i> -40...+80°C <i>(-40...+176°F)</i> -40...+120°C <i>(-40...+248°F)</i> 0...+100°C <i>(+32...+ 212°F)</i> -20...+180°C <i>(-4...+356°F)</i> -40...+180 °C <i>(-40...+356°F)</i> 0...+180°C <i>(+32...+356°F)</i> Special																
	8 Output units	Metric Non-metric																
9 Interface cable connection	Cable gland M20x1.5 for cable diameters 7.5 ... 12 mm Conduit fitting NPT1/2" (for wire conduits) Cable gland M20x1.5 for cable diameters 10 ... 15 mm																	
10 Ex certification and issuer	ATEX (VTT), Ex ia IIC T4 IECEX (VTT), Ex ia IIC T4 Factory Mutual (USA) CSA (Canada) TIIS (Japan) TR CU (EAC) KOSHA (Korean)																	
11 User's guide	English German French Finnish Swedish Japanese Russian Chinese Korean																	
12 Probe and cable length	2 m cable 5 m cable 10 m cable																	
13 Sensor type	HUMICAP 180R																	
Probe	14 (blank)																	
	15 Sensor protection	PPS plastic grid & stainless steel netting (recommended choice) PPS plastic grid Sintered stainless steel filter Stainless steel grid filter Membrane SST filter (for fuel cells)	<i>spare: DRW010281SP</i> <i>spare: DRW010276SP</i> <i>spare: HM47280SP</i> <i>spare: HM47453SP</i> <i>spare: 214848SP</i>															
	16 Probe installation accessories	None Duct installation kit Cable Gland ACRO Swagelok NPT 1/2" Swagelok ISO 3/8"	<i>spare: 210697</i> <i>spare: HMP247CG</i> <i>spare: SWG12NPT12</i> <i>spare: SWG12ISO38</i>															
TOTAL																		
QTY																		
TOTAL VALUE																		

Selections in bold are included in the prices of the basic versions.
 Selections in *italic* are available at an extra price.

Installation accessories	
Galvanic Isolator	212483
Barrier	210664
Protection Cover	214101
Rain Shield	215109

Example of order code with typical settings:

HMT360 | 7 | **A** | **2** | **2** | B | C | A | 1 | A | 2 | B | V | 5 | A | 1 | M

End customer: _____

HMT368 Humidity and Temperature Transmitter For pressurized pipelines



Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT360	8	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	PRICE	
Transmitter unit	1 Transmitter type	HMT368	8																	
	2 Parameters	RH+T RH+T+Td+a+Tw+x	A D																	
	3 Display	no display <i>display on transmitter cover</i>	1 2																	
	4 Number of analog outputs	1 analog output channel (Ch1) 2 analog output channels (Ch1 + Ch2)	4... 20 mA 4... 20 mA	1 2																
	5 Parameter and scaling for 6 analog output (Ch1 & Ch2)	No analog output RH (0... 100%RH) Temperature (choose range in next section) Td (-40...+100°C) a (0...500g/m3) Tw (0...+100°C) x (0...500g/kg d.a.)	(-40...+212°F) (0...218.5gr/ft3) (+32...+212°F) (0...3500gr/lb)																	
	Special:	Define quantity for: Define scale for:	CH1: _____ CH2: _____ CH1: _____ CH2: _____																	
	NOTE:	- Td, a, Tw and x are only available with parameter selection D - If only one analog output has been chosen, choose A for Ch2																		
	7 Analog output range for temperature	-40...+60°C -20...+60°C 0...+60°C -20...+80°C -20...+120°C -40...+80°C -40...+120°C 0...+100°C -20...+180°C -40...+180°C 0...+180°C Special	(-40...+140°F) (-4...+140°F) (+32...+140°F) (-4...+176°F) (-4...+248°F) (-40...+176°F) (-40...+248°F) (+32...+ 212°F) (-4...+356°F) (-40...+356°F) (+32...+356°F)																	
	8 Output units	Metric Non-metric		1 2																
	9 Interface cable connection	Cable gland M20x1.5 for cable diameters 7.5 ... 12 mm Conduit fitting NPT1/2" (for wire conduits) Cable gland M20x1.5 for cable diameters 10 ... 15 mm																		
10 Ex certification and issuer	ATEX (VTT), Ex ia IIC T4 IECEX (VTT), Ex ia IIC T4 Factory Mutual (USA) CSA (Canada) TIIS (Japan) TR CU (EAC) KOSHA (Korea)																			
11 User's guide	English German French Finnish Swedish Japanese Russian Chinese Korean																			
Probe	12 Probe and cable length	2 m cable 5 m cable 10 m cable 2 m cable 5 m cable 10 m cable	226 mm probe, max 180°C 226 mm probe, max 180°C 226 mm probe, max 180°C 448 mm probe, max 180°C 448 mm probe, max 180°C 448 mm probe, max 180°C																	
	13 Sensor type	HUMICAP 180R																		
	14 (blank)																			
	15 Sensor protection	PPS plastic grid & stainless steel netting (recommended choice) PPS plastic grid Sintered stainless steel filter Stainless steel grid filter Membrane SST filter (for fuel cells)																		
	16 Probe installation accessories	Ball valve set Fitting Body NPT1/2 Fitting Body ISO1/2																		
TOTAL																				
QTY																				
TOTAL VALUE																				

Selections in bold are included in the prices of the basic versions.
Selections in *italic* are available at an extra price.

Installation accessories	
Galvanic Isolator	212483
Barrier	210664
Protection Cover	214101
Rain Shield	215109

Example of order code with typical settings:

HMT360 8 A 2 2 B C A 1 A 2 B L 5 A 1 E

End customer: _____

HMT360 Humidity and Temperature Transmitter unit



Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT360	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	PRICE	
1 Transmitter type	HMT360		0																		
2 Parameters	RH+T RH+T+Td+a+Tw+x		A	D																	
3 Display	No display Display on transmitter cover			1	2																
4 Number of analog outputs	1 analog output channel (Ch1) 2 analog output channels (Ch1 + Ch2)	4... 20 mA 4... 20 mA																			
5 Parameter and scaling for 6 analog output (Ch1 & Ch2)	No analog output RH (0... 100%RH) T (choose range in next section) Td (-40...+60°C) (-40...+140°F) a (0... 160g/m3) (0...70gr/l3) Tw (0...+60°C) (+32...+140°F) x (0...160g/kg d.a) (0...1120gr/lb) Td (-40...+100°C) (-40...+212°F) a (0...500g/m3) (0...218.5gr/l3) Tw (0...+100°C) (+32...+212°F) x (0...500g/kg d.a) (0...3500gr/lb) Special: Define quantity for: CH1: _____ CH2: _____ Define scale for: CH1: _____ CH2: _____									A	B	C	D	E	F	G	H	J	K	L	X
NOTE:	- Td, a, Tw and x are only available with parameter selection D - If only one analog output has been chosen, choose A for Ch2																				
7 Analog output range for temperature	-40...+60°C (-40...+140°F) -20...+60°C (-4...+140°F) 0...+60°C (+32...+140°F) -20...+80°C (-4...+176°F) -20...+120°C (-4...+248°F) -40...+80°C (-40...+176°F) -40...+120°C (-40...+248°F) 0...+100°C (+32...+212°F) -20...+180°C (-4...+356°F) -40...+180°C (-40...+356°F) 0...+180°C (+32...+356°F) Special																				
8 Output units	Metric Non-metric																				1 2
9 Interface cable connection	Cable gland M20x1.5 for cable diameters 7.5 ... 12 mm Conduit fitting NPT1/2" (for wire conduits) Cable gland M20x1.5 for cable diameters 10 ... 15 mm																				A B C
10 Ex certification and issuer	ATEX (VTT), Ex ia IIC T4 IECEX (VTT), Ex ia IIC T4 Factory Mutual (USA) CSA (Canada) TIIS (Japan) TR CU (EAC) KOSHA (Korea)																				2 3 4 5 7 8 A
11 User's guide	English German French Finnish Swedish Japanese Russian Chinese Korean																				B C D E G J K V W
12 No probe																					0
13 (blank)																					0
14 (blank)																					0
15 (blank)																					0
16 (blank)																					0
																			TOTAL		
																			QTY		
																			TOTAL VALUE		

Selections in bold are included in the prices of the basic versions.
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMT360 | 0 | A | 2 | 2 | B | C | A | 1 | A | 2 | B | 0 | 0 | 0 | 0 | 0 | 0

End customer: _____

HMP360 Humidity and Temperature Transmitter series Probes



Vaisala HUMICAP® Humidity and Temperature Probe			HMP360	1	2	3	4	5	6	7	PRICE	
Probe	1 Probe type		HMP361	1								
			HMP363	3								
			HMP364	4								
			HMP365	5								
			HMP367	7								
			HMP368	8								
	2 Probe & cable length		HMP361									
			HMP363, +80°C	no cable		A						
				2 m cable	1							
				5 m cable	2							
				10 m cable	3							
			HMP363, +120°C	2 m cable		B						
				5 m cable		C						
				10 m cable		D						
			HMP364	2 m cable		E						
				5 m cable		F						
				10 m cable		G						
			HMP365	2 m cable		H						
				5 m cable		J						
				10 m cable		K						
		HMP367	2 m cable		V							
			5 m cable		W							
			10 m cable		X							
		HMP368	2 m cable		L							
			5 m cable		M							
			10 m cable		N							
			2 m cable		P							
			5 m cable		Q							
			10 m cable		R							
3 Sensor type		HUMICAP 180R						5				
4 (blank)									A			
5 Sensor protection		PPS plastic grid & stainless steel netting (recommended choice)								1		
		PPS plastic grid								2		
		Sintered stainless steel filter								3		
		Membrane SST filter (for fuel cells)								5		
6 Installation kit		No kit									A	
		HMP363/367	Duct installation kit for HMP363&367								B	
		HMP365	Mounting flange								D	
		HMP368	Ball valve set								E	
		HMP363/367	Cable Gland ACRO								J	
		HMP364	Fitting body								K	
		HMP364	NPT Fitting Body								G	
		HMP367	Swagelok NPT 1/2"								L	
		HMP367	Swagelok ISO 3/8"								M	
		HMP368	Fitting Body ISO1/2								N	
		HMP368	Fitting Body NPT1/2"								H	
7 Ex certification and issuer		ATEX (VTT), Ex ia IIC T4									2	
		IECEX (VTT), Ex ia IIC T4									3	
		Factory Mutual (USA)									4	
		CSA (Canada)									5	
		TIIS (Japan)									7	
		TR CU (EAC)									8	
		KOSHA (Korea)									A	
See latest Ex certificates at: www.vaisala.com/hmt360												
										TOTAL		
										QTY		
										TOTAL VALUE		

End customer: _____