UKR 90, UKRA 90 Universal clamps





UKR 90 Universal clamp.



UKJ Earthing plate.

Applications:





UKRS 90 Universal clamp with spacer.



Spacer.

UKR 90

Use

For fixing cables, tubes, hoses, etc. It will fix round profiles with Ø 20 – 90 mm or angular profiles with circumferences of 60 – 300 mm.


Design

The bracket is made of non-magnetic hot-dip galvanized steel. The band is made of stainless steel SS 2333-02 with rounded edges and has a thickness of 0.2 mm. The band can be tightened and locked in one operation. The locking bolt is made of die-cast zinc alloy.

UKRS 90


Consists of one UKR 90 and a spacer with a hexagon head wood screw for fastening on a wooden pole e.g.





UKRA 90 Universal clamp with bracket for anchor bar.

Designation	Weight kg/item
UKR 90	0.17
UKRA 90	0.23
UKS	0.28
UKRS 90	0.45
UKJ	0.14



Dimensional drawing of the anchor bar.

UKRA 90

Use

For fixing cables with \emptyset 20 – 90 mm to the anchor bars in a cable distribution cabinet, etc.

Design

The bracket is made of non-magnetic hot-dip galvanized steel. The band is made of stainless steel according to SS 2333-02 with rounded edges and has a thickness of 0.2 mm. The band can be tightened and locked in one operation. The locking bolt is made of die-cast zinc alloy. A spring-loaded nut with a reversible locking washer offers a choice of fixed or flexible position and direction.