



General Purpose

Ordering Part #	Thread Length (A)
70085-1010-001	1.125 (28.57)
70085-1010-003	2.625 (66.67)
70085-1010-018	3.625 (92.07)
70085-1010-118	5.000 (127.00)

(Select cable from group "A", see index)

Performance Curves





- Specifications:**
- Output Voltage (Standard): 40 V (P-P)
 - Output Voltage (Guarantee Point): 3.4 V (P-P)
 - DC Resistance: 130 ohms max.
 - Typical Inductance: 33 mH ref.
 - Output Polarity: Pin 'B' positive
 - Operating Temperature: -55 to +107°C
 - Net Weight: 5 oz. max.

High Sensitivity

Ordering Part #	Thread Length (A)
70085-1010-002	1.125 (28.57)
70085-1010-175	2.625 (66.67)
70085-1010-026	3.625 (92.07)
70085-1010-408	5.000 (127.00)

(Select cable from group "A", see index)

Performance Curves



- Specifications:**
- Output Voltage (Standard): 150 V (P-P)
 - Output Voltage (Guarantee Point): 12.9 V (P-P)
 - DC Resistance: 1500 ohms max.
 - Typical Inductance: 360 mH ref.
 - Output Polarity: Pin 'B' positive
 - Operating Temperature: -55 to +107°C
 - Net Weight: 5 oz. max.

Dimensions in inches and (mm).