





VALVOLE DI SICUREZZA
SAFETY VALVES
SOUPAPES DE SURETE
SICHERHEITSENTILE

| Disegno Drawing Dessin Zeichnung | N° Catalogo Part Number N° Catalogue Katalog Nr | Attacchi Connections Raccords Anschlüsse | | Sezione orifizio Orifice section Section orifice Öffnungs- querschnitt [mm ²] | Coefficiente di scarico Kd Discharge coefficient Kd Coefficient d'écoulement Kd Ausströmungsfaktor Kd | Campo taratura Set pressure range Champ de tarage Einstellbereich [bar] | PS [bar] | TS [°C] | | Confezione n° pz Package pcs Emballage Verpackung |
|---|--|---|----------|--|---|--|-------------|---------|------|---|
| | | IN | OUT | | | | | Min | Max | |
|  | 3030/88C | 1" NPT | 1.1/4" G | 298 | 0,83 | 8 → 50 | 55 | -50 | +150 | 8 |
| | 3030/66C | 3/4" NPT | 3/4" G | 113 | 0,9 | | | | | 15 |
| | 3030/44C | 1/2" NPT | 3/4" G | 113 | 0,9 | | | | | 15 |
| | 3030/44G (1) | 1/2" G | 3/4" G | 113 | 0,9 | 8 → 50 | | | | 15 |
|  | 3060/46C | 1/2" NPT | 3/4" G | 78,5 | 0,93 | 9 → 50 | 55 | -50 | +120 | 45 |
| | 3060/36C | 3/8" NPT | 3/4" G | 78,5 | 0,92 | | | | | 45 |
| | 3060/45C | 1/2" NPT | 5/8" SAE | 70,9 | 0,45 | | | | | 45 |
| | 3060/34C | 3/8" NPT | 1/2" SAE | 38,5 | 0,69 | | | | | 45 |
| | 3060/33C | 3/8" NPT | 3/8" SAE | 38,5 | 0,63 | | | | | 45 |
| | 3060/24C | 1/4" NPT | 1/2" SAE | 38,5 | 0,69 | | | | | 45 |
| | 3060/23C | 1/4" NPT | 3/8" SAE | 38,5 | 0,63 | | | | | 45 |
|  | 3061/2C | 1/4" NPT | 3/8" G | 44,2 | 0,89 | 11 → 60 | 70 | -50 | +150 | 18 |
| | 3061/3C | 3/8" NPT | 1/2" G | | | | | | | 18 |
| | 3061/4C | 1/2" NPT | 1/2" G | | | | | | | 18 |
|  | 3065/4C | 1/2" NPT | 1" G | 132,7 | 0,87 | 11 → 60 | 70 | -50 | +150 | 24 |
| | 3065/6C | 3/4" NPT | 1" G | | | | | | | 24 |

(1)
Prodotto a richiesta.

(1)
Product on request.

(1)
Produit sur demande.

(1)
Produkt auf Anfrage.