



Regulator 510 Ac pressure 0-2.5 bar

Product Group: 171

Product number: 510001

General description

Reduces cylinder pressure to suitable working pressure and keeps it constant

Features

- Provides constant flow of gas at right pressure
- Safety valve
- Comes with hose connections for 1/4" and 3/8"
- Built according to international norm EN ISO 2503 Class 3

Benefits

- No need for flame adjustment during work
- Provides safe working conditions
- Connects to all standard hose dimensions
- Long lasting quality

Technical data

Max.inlet pressure bar	15
Outlet pressure bar:	0-2.5
Safety outlet opens at bar	3-4
Max.capacity m3/h	5
Cylinder connection	3/4" BSP

Unitor cylinder regulators for acetylene and oxygen are designed for reliability and safety in use. The large adjustment knobs are red for acetylene and blue for oxygen for easy identification of gas type. Both contents and working pressure gauges are clearly graded in psi and bar.

All regulators are delivered with spare washers, hose connection for 1/4" and 3/8", gas hoses and instructions for use. Unitor regulators ensure a correct and stable working pressure with sufficient capacity for all types of gas welding and cutting work.

- Easy identification of gas types with colour-coded adjustment knobs
- Immediate identification of gas pressure with easy to read gauges marked both in psi and bar
- Full capacity for all types of gas welding and cutting work
- Designed for use with Unitor gas cylinders
- Full conformance with EN ISO 2503

Safety



Regulator 510 Ac pressure 0-2.5 bar

For safety reasons we strongly recommend to preform annual checking and testing of the regulator, and to change the regulator every 5 years

Accessories

Product number	Product name
550152	WASHER NYL 10 PCS FOR AC REGULATOR
550186	CONTENTS GAUGE AC 0-40 BAR
550202	WORKING GAUGE AC 0-2.5 BAR
619379	MANOMETER/GAUGE GUARD +

Documentation

Type	Document	Size
Instructions	PDF	166 KB