


## Datasheet for: KHF-12


**Safety ball valve with spring reset, nickel-plated brass, Rp 1/2**

Safety ball valve with spring reset, nickel-plated brass, Operating temperature -40 °C to 170 °C, Rp 1/2, DN 15, PN max. 65 bar 2/2-way safety ball valves, two parts, made of nickel-plated brass with spring return. The ball valve is closed in the normal position and opens against spring force. High safety standard because the valve is automatically closed if the handle is not operated; inadvertent opening is prevented.

Article number	103229
Type number	KHF-12
EAN/barcode	 4047322370042
Your price	54.35 € / Pcs

**Minimum order quantity**

Price Unit	1
Quantity Unit	Pcs
Packaging Unit	1
Content	1 Pcs
Minimum order quantity	1

**Productdata**

DN	15
A [mm]	100
B [mm]	43
Ball	Chrome-plated brass
Ball seal	PTFE
CAS no. SVHC 1	7439-92-1
Hand lever	Steel - PVC coated
Housing	Nickel-plated brass
L [mm]	75
Max. operating temperature [°C]	170
Min. operating temperature [°C]	-40
PN [bar]	65
Page No.	HK291
REACH Info	contains SVHC substance
REACH SVHC1 substance name	lead
REACH compliant	no
RoHS materials notice	RoHS compliant

Spring	Stainless steel 1.4301
Standard thread	Rp thread acc. to ISO 7-1
Stem seal	FKM
Thread	Rp 1/2
Thread material	Nickel-plated brass
country of origin	IT
customs tariff number	84818081

## Variants

Article number	Thread	PN [bar]	Price
103229	Rp 1/2	65	54.35 € / Pcs
103234	Rp 2	40	323.38 € / Pcs
103230	Rp 3/4	65	71.05 € / Pcs
103228	Rp 3/8	65	54.35 € / Pcs
103231	Rp 1	65	105.29 € / Pcs
103233	Rp 1 1/2	40	212.45 € / Pcs
103232	Rp 1 1/4	40	157.10 € / Pcs
103227	Rp 1/4	65	54.35 € / Pcs

## More Pictures

