



## Accu grease gun with ZBH

20 V-2000 mAh

**Item number:** 18 051  
**EAN:** 4103810180514  
**Discount group:** D

### Technical data

**Grease pump piston actuation:** electric motor driven by a 20 V accumulator ensures continuous grease supply

**Refilling options:** 400 g grease cartridge, DIN 1284, or bulk grease

**Delivery rate (g/min):** approx. 150

**Delivery per accu load:** approx. 25 cartridges of 400 g (without counter pressure)  
 approx. 7 cartridges of 400 g (at approx. 100 bar counter pressure)

**Operating pressure max. (bar/psi):** 400 / 5800

**Maximum pressure (bar/psi):** 680 / 10000

**Charging time:** approx. 60 minutes

**High performance accumulator:** 2000 mAh

**Grease supply hose:** 11 x 1000 mm

**Operation of push rod:** with T-grip

**Cover:** loose

**Wall thickness of grease gun tube (mm):** 1

**Dimensions LxWxH (mm):** 380 x 205 x 110

**Weight of accu grease gun, empty (kg):** 3,56

### Charger

**Input voltage (V):** 230 V AC

**Frequency (Hz):** 50/60

**Input current max. (A):** 0,5

**Input power max. (W):** 45

**Output voltage (V):** 16-21 V DC

**Output current (A):** 1,5

**Connecting cable with Euro two-pin plug, length (m):** 1,6

**Dimensions without cable LxWxH (mm):** 180 x 120 x 85

**Weight (kg):** 0,455

### Accu

**Capacity:** 2000 mAh

**Voltage (V):** 20

**Accu:** lithium-ion accumulator


**Charging time:** approx. 60 minutes

**Dimensions LxWxH (mm):** 118 x 76 x 45

**Weight (kg):** 0,378

### Specification

- Electric motor driven by a 20 V accumulator
- 2 lithium-ion accumulators 20 V, 2000 mAh (18 051 100)
- Filling nipple (12 672) and ventilating valve (85 277)
- High-pressure grease supply hose with anti-kink spring, 11 x 1000 mm (18 042)
- Precision machined coupler, 4 claws, M 10 x 1 female (12 643)
- Retention adapter, G 1/8" female, M 10 x 1 male (12 016) and retention adapter, NPT 1/8" female, M 10 x 1 male (12 020)
- Grease gun tube galvanized
- Accu charger 230 V (18 051 200)
- The grease gun is equipped with a stand and a hose holder
- Support foot for easy handling, stable support
- 1 Carrying strap
- Packed in plastic case, black





### Special notes

- Operates with greases up to NLGI grade 2 at 20°C
- Integrated display with grease flow meter, battery charge indicator and indication of grease delivery
- Display blinks red in the event of counter pressure or when the power consumption is too high
- Alarm in the event of grease leakage – Grease volume meter remains unchanged
- 2 adjustable grease supply speeds (L - H)
- Molded seal for absolute tightness when using bulk grease or cartridges
- The accumulator's charging level is indicated at the grease gun and at the accumulator
- Safe handle on the push rod
- Optimum localisation of the lubrication area by LED light, e.g. in case of difficult to access grease nipples or poor lighting conditions
- Anti-kink springs prevent kinks in the hose and extend its service life
- Venting over venting valve or quick and easy screwing-in by 1,5 turns of the tube

### Packaging

Dimensions case LxWxH (mm): 545 x 260 x 100

Weight (kg) with accessories and case: 6

Packing unit: 1,0